



TECHNICAL DATA SHEET

GRODAL SS CUT 10 (T)

SYNTHETIC COOLANT

DESCRIPTION

Grodal SS Cut 10(T) is a synthetic coolant, developed for use as a grinding and heavy duty machining fluid for ferrous metals. This product is replacement for neat cutting oils in application such as gun drilling, gear hobbing and broaching.

APPLICATION

Grodal SS cut 10 (T) is used for grinding cast iron & steel. It is recommended for honing, milling, turning, boring, drilling, tapping, gear hobbing and broaching on all ferrous alloys.

BENEFITS

- | Excellent Rust/corrosion protection.
- | Provides superior machining on difficult alloys such as Nickel and titanium.
- | Chlorine and phenol free.
- | Longer sump life.

TECHNICAL DATA

Appearance	:	Clear Colourless Liquid
Sp. Gravity @30°C	:	1.07 – 1.17
pH (Neat)	:	8 - 10
Solution in 2 % water	:	Clear

RECOMMENDATIONS

Grinding : 4 - 6%
General machining : 4 - 10 %
Broaching : 10 - 15%
The concentration of this product solution can easily checked by using refractometer. Maintain concentration and avoid contact with strong oxidizers.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 04.03.2015

Supersedes all earlier

GRAUER & WEIL (INDIA) LIMITED

Registered Office : 'Growel House', Akurli Road, Kandivli (E), Mumbai - 400 101, India
Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11, E-mail : lubricants@growel.com,
Website : www.growel.com