



# TECHNICAL DATA SHEET

## GRODAL GPS 40

### RUST PREVENTIVE

#### DESCRIPTION

Grodal GPS 40 is a mixture of additives in high grade hydrocarbon distillate. It is an all purpose liquid for displacing moisture, corrosion control, lubrication cleaning and penetration. This product leaves oily protective film with significant corrosion inhibition properties.

#### APPLICATION

Grodal GPS 40 is a soft oily film coating product. It is recommended for protection of mechanical parts, switches, spark plugs, machine shop and tool manufacturers. It can be used on door hinges, locks, wheels, chairs and toys.

#### BENEFITS

- Easy application
- Provides protection by displacing water
- Easy removal
- Excellent non staining property
- Stops Squeaks
- Loosen rusty parts

#### TECHNICAL DATA

Colour and Appearance	:	Yellow liquid
Sp. Gravity @ 30 °C	:	0.81- 0.84
Viscosity @ 40 °C	:	4 - 5 Cst.
Film type	:	Oily
Flash point	:	40 deg C.

#### RECOMMENDATIONS

Grodal GPS 40 is recommended to apply by dip method or spray leaving a protective film on component. This protective film can be removed by solvent or suitable alkaline cleaner.

#### SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

*Issued on : 21.09.2010*

*Supersedes all earlier*

**GRAUER & WEIL (INDIA) LTD. (Lube Division)**

**Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India**

**Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,**

**E-mail : lubricants@growel.com, Website : www.growel.com**