

# TECHNICAL DATA SHEET

# **GRODAL BROACH 1**

**BROACHING OIL** 

#### **DESCRIPTION**

GRODAL BROACH 1 is superior quality neat oil blended from high flash and low volatility mineral base oils. It contains high EP and antioxidant additives for long life.

#### **APPLICATION**

GRODAL BROACH 1 is suitable in machine tool lubrication and threading operations. It has been formulated to give excellent anti-wear and EP characteristics to cover a broad range of metal cutting operations. It can be used for honing and automatic lathe work also deep hole drilling on steels and non ferrous metals

### **BENEFITS**

- High oxidation stability.
- Preventing sludge formation during the operation for long period.
- Will not give excessive fumes or froth.
- No corrosion
- Good surface finish

## **TECHNICAL DATA**

Appearance : Yellow to Brown oil

Sp. Gravity @30°C : 0.84 – 0.87 Viscosity @40 °C : 18 - 23 cSt.

Flash Point COC °C : Above 140

# **ADVICES**

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

#### **SAFETY**

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on: 01.10.2010 Supersedes all earlier

Registered Office: 'Growel House', Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel.: 91 - 22 - 66993000 , Fax: 91 - 22 - 669930101/11, E-mail: lubricants@growel.com, Website: www.growel.com