



TECHNICAL DATA SHEET

GRODAL GEAR 32

INDUSTRIAL GEAR OIL

DESCRIPTION

Grodal Gear 32 is blended from high quality paraffin base oil and effective EP additive package designed to minimize wear of enclosed gears operated under heavy loads.

APPLICATION

Grodal Gear 32 lubricants are recommended for a variety of gears including spur, bevel, helical, worm and industrial hypoid gear cases on mobile contractor type equipment, cement mills, crushers, hoists, conveyers, winches and marine equipments.

BENEFITS

- Extreme pressure properties to minimise wear.
- Long oxidative and thermal service life.
- Protection against rust and corrosion.
- Resistance to foaming.

TYPICAL TECHNICAL DATA

Appearance	:	Clear Yellow liquid
Sp. Gravity @30°C	:	0.87
Viscosity @40 °C	:	32 cSt.
Viscosity Index	:	96
Flash Point COC °C	:	200 °C
Pour Point °C	:	-9
Foam test	:	Pass

RECOMMENDATIONS

Meets the requirements of # AGMA 250.04
DIN 51517 Part 3
U. S. Steel 224.

ADVICE

Store at ambient temperature and away from direct contact of fire. Avoid contact with water.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 19.09.2011

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House', Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com