



TECHNICAL DATA SHEET

GRODAL RPOB 20

RUST PREVENTIVE

DESCRIPTION

Grodal RPOB 20 is a oil based type of rust preventive. This product leaves oily protective film with significant corrosion inhibition properties.

APPLICATION

Grodal RPOB 20 is used as a short term inter-operational protective or for the treatment of components before wrapping or as a temporary protection of ferrous bar, rod, strip. The product is also suitable as flushing oil for the internal protection of engines and machinery. Grodal RPOB 20 is normally applied by immersion, brushing or spraying.

BENEFITS

- Easy application
- Provides excellent protection to assemblies.
- Easy removal
- Excellent non staining property
- Good resistance to salt water

TECHNICAL DATA

Colour and Appearance	:	Brown Liquid
Sp. Gravity @ 30 °C	:	0.84 - 0.88
K. Viscosity @ 40 °C	:	Maximum 16 cst.
Indoor Protection	:	6 Months
Outdoor Protection	:	2 Months
Film type	:	Oily
Flash Point	:	Minimum 120°C
Copper Strip Corrosion	:	1

RECOMMENDATIONS

Grodal RPOB 20 is recommended to apply by dip or spray method to give a protective film on component. This protective film can removed by solvent or suitable alkaline cleaner.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 21.09.2010

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com