



TECHNICAL DATA SHEET

GRODAL HYDRA AW 220 HYDRAULIC OIL

DESCRIPTION

Grodal Hydra AW 220 is a light colored, premium quality, anti wear hydraulic fluid formulated from high quality paraffin base stock with excellent stability, good resistance to oxidation and moisture with high natural viscosity index. It contains specifically selected anti-foamant, anti-rust, anti-oxidant and zinc type anti wear agent.

APPLICATION

Grodal Hydra AW 220 is formulated as a superior heavy duty anti wear hydraulic oil for use in modern high pressure hydraulic systems. It also provides good anti-rust and water separation properties. It acts as a medium for transmitting power. It is recommended to handle the most severe hydraulic applications and satisfy many other lubrication applications. This product meet the following specifications

Vickers Vane Pump Test

Denison HF0, HF1 and HF2

DIN 51524 PART 2 and PART 3

BENEFITS

- Good oxidation stability for long service life.
- Resistance to sludge and varnish deposits
- Minimizes wear and scoring
- Corrosion and wear protection for components

TYPICAL TECHNICAL DATA

| | | |
|---------------------|---|--------------|
| Colour & Appearance | : | brown liquid |
| Sp.Gravity @ 30°C | : | 0.90 |
| Flash Point | : | 210°C min. |
| Viscosity @40 °C | : | 220 CST |
| Viscosity Index | : | 96 |
| Pour point | : | - 3 |
| Demulsibility | : | passes |
| Copper corrosion | : | 1a |
| Rust test | : | passes |

RECOMMENDATIONS

Grodal Hydra AW 220 is recommended for all industrial and mobile hydraulic system application. Due to incompatibility of silver and zinc containing oils, Grodal Hydra AW 220 should not be used in systems incorporating silver coated components.

MAINTENANCE

Grodal Hydra AW 220 is designed for long service life but it is known that all hydraulic oils eventually degrade due to the effect of oxidation. The symptoms of oil oxidation are an increase in viscosity, increase in acidity or the formation sludge.

SAFETY

This oil is unlikely to present any significant health or safety hazard when properly used in the recommended application as well as good standards of industrial and personal hygiene is maintained.

Issued on : 08.08.2011

Supersedes all earlier

GRAUER & WEIL (INDIA) LTD. (Lube Division)

Registered Office : 'Growel House' , Akurli Road, Kandivli (E), Mumbai - 400 101, India

Tel. : 91 - 22 - 66993000 , Fax : 91 - 22 - 669930101/11,

E-mail : lubricants@growel.com, Website : www.growel.com