

MECHZINC RANGE



SUBSTITUTE YOUR HOT DIP
GALVANISED COATING NEEDS WITH
MECHANICAL ZINC COATING



TRUST THE LEADER IN SURFACE FINISHING

MECHANICAL ZINC RANGE

- Produces adherent, smooth fine grained zinc deposit through tumbling in barrel.
- Deposit thickness achievable – 5 to 110 micron.
- Range includes specialized Preconditioner with lower foaming ability & Inhibitors – reduces hydrogen generation.
 - Deposits are porous in nature.
 - Virtually free from hydrogen embrittlement.
 - Post process baking is not important.
- No chelates / Complexing agent – simplified waste treatment.
- Shorter processing sequence.
- Lower chemical consumption.
- Suitable for smaller components – weight: 0.5 kg.& size: lesser than 6 – 8 inch.



Grauer & Weil (India) Limited

Growel Corporate, Akurli Road, Kandivli (E), Mumbai 400101, India

T 91 22 66993000 **F** 91 22 66993010 **E** info@growel.com

www.growel.com

Chemicals | Engineering | Paints | Lubes | Real Estate



DISCLAIMER: Our recommendations are made in good faith and are based on our skills. However, since the conditions of use of these products are beyond our control and may vary significantly in different situations, this information is given on the express condition and agreement that Grauer & Weil (India) Limited, will not be liable to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent rights.